

Data Sheet

Analytical line / Calorimeters



C 2000 basic version 2

The C 2000 basic IKA- calorimeter is a combustion calorimeter for determining gross calorific values of liquid and solid samples. A high level of automation with extremely simple handling characterizes this instrument. In addition to the isoperibolic measurement procedure (static jacket), a dynamic (reduced-time) working method is also available. To provide the calorimeter with cooling water, it needs to be connected to a thermostat f.e. IKA KV 600 (accessory) or a firmly installed water connection. The C 2000 basic is equipped with a very convenient console to operate the unit.

- Automatic water handling system includes tempering, filling and emptying of calorimeter inner vessel
- Automatic oxygen filling of decomposition vessel
- Automatic decomposition vessel identification
- Automatic sample ignition
- Validation according to DIN 51900, ISO 1928, ASTM D240, ASTM D4809, ASTM D5865, ASTM D1989, ASTM D5468, ASTM E711
- Working methods:
isoperibol, measurement time: approx. 22 min
dynamic, measurement time: approx. 7 min
- Compact, integrated modular design for convenient operation
- Cooling water supply via thermostat f.e. IKA KV 600 (accessory) or firmly installed water connection (C 25 pressure regulating valve recommended)
- Interface connections for each of the following: scale, printer, monitor and sample rack C 5020
- User-friendly software C 5040 CalWin for controlling the calorimeter and administration of measuring data
- Up to eight measurement cells can be controlled by a single PC, using a multi-serial plug-in card PCI 8.2 (accessory)
- LIMS integration is possible
- Special halogen resistant vessel for quantitative decomposition of halogens and sulfur
- The decomposition vessel can be changed over to use combustible crucibles C 14 (accessory C5010.4 is needed)
- Consumables for calibrations and initial operation are included with delivery.

Accessories: C 5010 Decomposition vessel, standard, C 5012 Decomposition vessel, halogen resistant, C 5010.4 Attachment for combustible crucible C14, C 5010.5 Crucible holder, big, C 5030 Venting station, C 5020 Sample rack, KV 600 cooling water supply, C 5040 CalWin, C 5041.10 Connection cable, C 21 Pelleting press, C 29 Pressure gauge, oxygen, C 25 Pressure regulating valve, C 60 Conversion set for C 62, C 5003.1 Aqua Pro stabilizing agent, C 710.4 Cotton thread, cut to length, C 5010.3 Ignition wire, spare, C 5012.3 Ignition wire, platinum, C 4 Quartz dish, C 6 Quartz crucible, big, C 5 Set of VA combustion crucibles, C

Technical Data

| | |
|--|-----------------|
| Measuring range max. [J] | 40000 |
| Measuring mode adiabatic 22°C | no |
| Measuring mode isoperibol 22°C | no |
| Measuring mode dynamic 25°C | yes |
| Measuring mode isoperibol 25°C | yes |
| Measuring mode dynamic 30°C | yes |
| Measuring mode isoperibol 30°C | yes |
| Measuring mode double dry (ISO 1928) | no |
| Measuring time dynamic approx. [min] | 7 |
| Measuring time isoperibol approx. [min] | 22 |
| Reproducibility dynamic (1g benzoic acid NBS39i) [%RSD] | 0.1 |
| Reproducibility isoperibol (1g benzoic acid NBS39i) [%RSD] | 0.05 |
| Working temperature max. [°C] | 30 |
| Temperature measurement resolution [K] | 0.0001 |
| Cooling medium temperature min. [°C] | 12 |
| Cooling medium temperature max. [°C] | 28 |
| Cooling medium permissible operating pressure [bar] | 1.5 |
| Cooling medium | tap water |
| Type of cooling | flow |
| Flow rate min. [l/h] | 0.3 |
| Flow rate max. [l/h] | 70 |
| Oxygen operating pressure max. [bar] | 40 |
| Interface scale | RS232 |
| Interface printer | Centronix |
| Interface PC | RS232 |
| Interface test rack | yes |
| Interface ext. monitor | yes |
| Interface ext. keyboard | yes |
| Oxygen filling | yes |
| Degasification | no |
| Decomposition detection | yes |
| Decomposition vessel C 5010 | no |
| Decomposition vessel C 5012 | yes |
| Decomposition vessel C 7010 | no |
| Decomposition vessel C 7012 | no |
| Decomposition vessel C 62 | no |
| Analysis according to DIN 51900 | yes |
| Analysis according to ASTM D240 | yes |
| Analysis according to ASTM D4809 | yes |
| Analysis according to ASTM D1989 | yes |
| Analysis according to ASTM D5468 | yes |
| Analysis according to ASTM D5865 | yes |
| Analysis according to ASTM E711 | yes |
| Dimensions (W x H x D) [mm] | 440 x 500 x 450 |
| Weight [kg] | 30 |
| Permissible ambient temperature [°C] | 20 - 25 |
| Permissible relative moisture [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| RS 232 interface | yes |
| Voltage [V] | 220 - 240 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 1800 |

Ident. No.

0008801900

710.2 Set of VA combustion crucibles, C 723 Benzoic acid, blister package, C 723 Benzoic acid BIG Package, C 43 Benzoic acid NBS 39i, C 9 Gelatine capsules, C 10 Acetobutyrate capsules, C 12 Combustion bags 40 x 35 mm, C 12 A Combustion bags 70 x 35 mm, C 14 Combustible crucible, C 15 Paraffin strips, C 16 Parafilm, C 17 Paraffin, AOD 1.11 Control standard, AOD 1.12 Control standard, C 26 Prep Stand